



STRIP RETROFIT KIT

JAYKAL

PROJECT NAME:

JAYKAL LED SOLUTIONS, INC.

www.jaykal.net

PROJECT NOTES:

26832 Lewes Georgetown Hwy,
Building 2, Unit E
Harbeson, DE 19951
(P) 302-295-0015
(F) 302-295-0016

FEATURES & BENEFITS

- ◆ Available in 10W to 60W Fixed Wattage or with Multi-Wattage Driver
- ◆ CCT: 3000K, 3500K, 4000K, 5000K
- ◆ 130+lm/W
- ◆ 0-10V Dimming optional
- ◆ 5 Year Standard Warranty with 10 Year Available
- ◆ Replacement Housings for existing strip fixtures are available by request. Please add an H to the end of the part number.



Revised 1/20/21

Specifications are typical values and may change without notification

efficiency. illuminated.

STRIP RETROFIT KIT



JAYKAL

SPECIFICATIONS TABLE

MODELS	JLS68102-STR (10W-60W)			
INPUT VOLTAGE	100-277VAC 50/60hz			
WATTAGE	M1 (12W/16W/20W/24W)	M2 (18W/24W/30W/36W)	M3 (24W/30W/36W/40W)	M4 (40W/45W/50W/60W)
LENGTHS	2/3/4 Foot	3/4/8 Foot	3/4/8 Foot	4/8 Foot
EFFICACY	130lm/W			
LUMENS	1,560LM to 3,120LM	2,340LM to 4,680LM	3,120LM to 5,200LM	5,200LM to 7,800LM
L70 HOURS	113,000 hrs. +			
POWER FACTOR	>0.9			
THD	<15%			
CRI	>80			
CCT	3000K/4000K/5000K			
OPERATIONAL TEMP.	-30°C - 50°C			
HOUSING MATERIAL	Steel			



ORDERING GUIDE

MODEL	WATTAGE	LENGTH	CCT	DIMMING	CHANNEL WIDTH	OPTIONS
JLS68102-STR	VARIABLE WATTAGE M1 = (12W/16W/20W/24W) M2 = (18W/24W/30W/36W) M3 = (24W/30W/36W/40W) M4 = (40W/45W/50W/60W) VARIABLE WATTAGE EMERGENCY EM1 = (12W/16W/20W/24W) EM2 = (18W/24W/30W/36W) EM3 = (24W/30W/36W/40W) EM4 = (40W/45W/50W/60W) FIXED WATTAGE XX = May be 10W to 60W	2 = 2 FT. 3 = 3FT. 4 = 4FT. 8 = 8FT.	30K = 3000K 35K = 3500K 40K = 4000K 50K = 5000K	N = No Dimming 10 = 0-10V P = Power Line 50 = 50/50 Dimming	S = Standard 4.25 Inches C = Custom Enter Dimension to the nearest 1/8th inch. Example: C4.75 = 4 3/4 Inches	Blank = No Option OC = Occupancy Sensor OCBL = Occupancy Bi-Level Dimming OCAL = Occupancy Bi-Level Dimming with Grouping



Not all product variations listed on this page are DLC qualified. Visit www.designlights.org/search to confirm qualification.

Contact Jaykal for additional product approval.

Specifications are typical values and may change without notification

efficiency. illuminated.