

# WRAP FIXTURE



**JAYKAL**

PROJECT NAME:

**JAYKAL LED SOLUTIONS, INC.**

[www.jaykal.net](http://www.jaykal.net)

PROJECT NOTES:

26832 Lewes Georgetown Hwy,  
Building 2, Unit E  
Harbeson, DE 19951  
(P) 302-295-0015  
(F) 302-295-0016

## DESCRIPTION:


A cost effective LED lighting solution designed to deliver general ambient lighting for surface-mount ceiling applications in industrial applications. This model provides reliable color consistency and years of worry free life. This solution provides the look similar to that of an existing fluorescent fixture, but provide all of the great benefits of LED technology: energy-savings, long life, and maintenance savings. Three esthetic choices are offered, but all feature the same light engine.

## FEATURES & BENEFITS:

- ◆ Wattage Options: 24, 40 Watt
- ◆ CCT Options: 3000K, 4000K, 5000K
- ◆ 120 lm/W
- ◆ Options: 0-10V Dimming / Occupancy Sensor / Emergency Backup
- ◆ 5 Year Warranty
- ◆ Near Zero Maintenance



Standard Option



Architectural Option



Industrial Option



5 YEAR STANDARD WARRANTY—EXTENDED WARRANTIES AVAILABLE

(P) 302-295-0015 | (E) [sales@jaykal.net](mailto:sales@jaykal.net) | (W) [www.jaykal.net](http://www.jaykal.net)

*Specifications are typical values and may change without notification*

**efficiency. illuminated.**


# WRAP FIXTURE




**JAYKAL**

**SPECIFICATIONS TABLE**


| Model.                   | 24W                | 40W                |
|--------------------------|--------------------|--------------------|
| Input Voltage            | 100-277VAC 50/60hz | 100-277VAC 50/60hz |
| Wattage                  | 24W                | 40W                |
| Efficacy                 | 120 lm/W           | 120 lm/W           |
| Lumens                   | 2,880 lm           | 4,800 lm           |
| Power Factor             | >0.9               | >0.9               |
| THD                      | <15%               | <15%               |
| CRI                      | >80                | >80                |
| CCT                      | 3000K/4000K/5000K  | 3000K/4000K/5000K  |
| Operational Temperatures | -30°C — 50°C       | -30°C — 50°C       |
| Housing Material         | Aluminum           | Aluminum           |



**Industrial Option**



**Architectural Option**



**Standard Option**

## ORDERING GUIDE

| MODEL NUMBER  | - | WATTAGE  | - | CCT  | - | OPTIONS   | - | HOUSING TYPE   |
|---------------|---|--|---|--|---|---|---|--|
| JLS68102-WRAP |   | <b>242</b> = 24W (2ft)<br><b>244</b> = 24W (4ft)<br><b>404</b> = 40W (4ft) |   | <b>30K</b> = 3000K<br><b>40K</b> = 4000K<br><b>50K</b> = 5000K |   | <b>Blank</b> = No Option<br><b>OC</b> = Occupancy Sensor On/OFF<br><b>OBD</b> = Occupancy Sensor Bi-level Dimming<br><b>EM</b> = Emergency Backup |   | <b>BLANK</b> = Standard<br><b>A</b> = Architectural<br><b>IND</b> = Industrial |

(P) 302-295-0015 | (E) sales@jaykal.net | (W) www.jaykal.net

Specifications are typical values and may change without notification

**efficiency. illuminated.**