30 WATT LED FLOOD LIGHT



	JAYKAL
PROJECT NAME:	JAYKAL LED SOLUTIONS, INC.
	www.jaykal.net
PROJECT NOTES:	26832 Lewes Georgetown Hwy, Building 2, Unit E
	Harbeson, DE 19951
	(P) 302-295-0015
	(F) 302-295-0016

FEATURES & BENEFITS

- ♦ Lumileds LEDs Offer High Luminous Efficiency and Long Life.
- ♦ Lumen Package 114lm/W
- ♦ High Efficiency LED Driver
- ♦ Wide Voltage Input: 100-277VAC
- ♦ Cast Aluminum Construction Provides Superior Cooling Performance, LED Tj<85
- Excellent Optical Design Optimizes Light Utilization and Distribution.
- Photocell Control Available (Option)














Revised 2/14/20

30 WATT LED FLOOD LIGHT



					JAYKAL				
SPECIFICATIONS TABLE									
WATTAGE	30W	LUMENS	3,409lm	EFFICACY	114lm/W				
INPUT VOLTAGE	100-277VAC 50/60hz	POWER FACTOR	0.95	CRI	> 80				
THD	< 14 %	сст	3000K / 4000K / 500	OK / 4000K / 5000K / 6500K					
LIFE (L70)	50,000 hours	LIGHTING ANGLE	101°	OPERATIONAL TEMP.	-30°C -+45°C				
HOUSING FINISH	Dark Bronze / White			PROTECTION	IP65				
HOUSING MATERIAL	Aluminum Die-cast	LENS MATERIAL	Polycarbonate	ENVIRONMENT	Wet Locations				
WEIGHT	3.04 lbs.	DIMENSIONS	9.06 x 7.4 x 1.78 in						
		WARRANTY	5 Year Standard, 10 Year Available						



ORDERING GUIDE EXAMPLE: JLS68103-G2FL-30-277-50K-D-K-PC								30-277-50K-D-K-PC		
MODEL		VOLTAGE	-	ССТ	-	FINISH		MOUNT	-	CONTROL
JLS68103-G2FL-30		277 = 120-277VAC		30K = 3000K		D = Dark Bronze		K = Knuckle		BLANK = None
				40K = 4000K		W = White		T = Trunnion		PC = Photo Cell
				50K = 5000K						
				57K = 5700K						



Not all product variations listed on this page are DLC qualified. Visit www.designlights.org/search to confirm qualification. Contact Jaykal for additional product approval.